



Nitrogen removal via nitrite from reject water produced after dewatering of thermally hydrolyzed and digested sludge

E. Statoris, C. Noutsopoulos, D. Mamais, A. Andreadakis, S. Malamis
 National Technical University of Athens
 Haifa, Israel, 15 October 2018

15th Specialized Conference on
Small Water & Wastewater Systems

7th Specialized Conference on
Resources Oriented Sanitation



When reject water recycling becomes an issue - Psyttalia WWTP





Equivalent population



- Design, average: 3 800 000


Sludge Treatment Processes


- Thickening
 - Thermal hydrolysis of 50% of secondary sludge
 - Digestion
 - Dewatering
 - Thermal drying
- Sludge reject water produced from the above processes is recycled and it increases the inlet nitrogen load of the plant by >20%


















SBR operating conditions



Parameter	Start-up (Days 1-85)	1 st period (Days 85-185)	2 nd period (Days 185-258)	3 rd period (Days 260-290)
pH	8.4±0.15	8.3±0.3	8.3±0.2	8.4±0.2
Carbon source	Acetic Acid	Acetic Acid & Thickened reject water	Acetic Acid	Acetic acid
HRT	15.4±5.4	6.7 ±2.2	5.2±0.74	3.7±0.27
NLR_TKN (kg N m ⁻³ d ⁻¹)	0.09±0.06	0.32±0.11	0.35±0.10	0.51±0.11
NLR_NH ₄ -N (kg N m ⁻³ d ⁻¹)	0.07±0.05	0.24±0.08	0.23±0.04	0.40±0.03
DO (mg L ⁻¹)	>2	>2	>2	>2
MLVSS (mg L ⁻¹)	1635±866	4807±944	5287±1038	5689±509











AOB and NOB population dynamics calculated by FISH technique



- ❑ The bacterial population of **AOB** increased from 23.4% to 35.6% while the **NOB** population decreased from 36.9% to 9.9% as the conventional nitrification replaced by the nitritation/denitrification process.



Conclusions



The pilot scale SBR operated under stable conditions achieving:

- Average NLR up to $0.5 \text{ kgNH}_4\text{-N m}^{-3} \text{ d}^{-1}$ with HRT less than 4 days
- $\text{NH}_4\text{-N}$ removal: >85%
- TN removal: >65%
- Ammonia uptake rates (AUR) up to $9 \text{ mgN gVSS}^{-1} \text{ h}^{-1}$
- Nitrite uptake rates (NUR) up to $15 \text{ mgN gVSS}^{-1} \text{ h}^{-1}$






SMART Plant Project



SMART-Plant has received funding from the European Union's **Horizon 2020** Research and Innovation Programme





Thank you!!!

15th Specialized Conference on
Small Water & Wastewater Systems

7th Specialized Conference on
Resources Oriented Sanitation

